Reference Number: 150925-BH1

Prepared: 2012年6月10日 Revised: 2018年3月30日

Product name: H1 Bell Hammer Spray 420 ml

1. Chemical substances and company information

Product name: H1 Bell Hammer Spray 420 ml

Company name: Suzuki Kikoh Co., Ltd.

Address: 316-3 Matsuhidai, Matsudo, Chiba Prefecture 270-2214

Department in charge:

Emergency telephone No. Telephone No.: 047-385-5311 FAX No.: 047-385-5313

2. Hazards identification

GHS classification of products, label elements

GHS Classification

Physio-chemical hazard Aerosol: Category 1

Health Hazards Specific target organ toxicity (single exposure): Category 2

Specific target organ toxicity (single exposure): Category 3 (Anesthetic acti-

Specific target organ toxicity (single exposure): Category 1

GHS Label Elements







Signal word Hazard

Hazard information Extremely highly combustible or flammable aerosol.

High-pressure container; may explode if heated.

May cause organ damage.

May cause drowsiness or dizziness.

Prolonged or repeated exposure may cause organ damage.

Physical and chemical hazards Contains high pressure flammable gas. May explode upon heating or impact.

Contains flammable gas. Retained gas may explode. May ignite or burn when exposed to high temperatures.

3. Composition and information on ingredients

Classification of chemical substance or mixture

Composition and content

Ingredient name / Chemical name	Content (%)	CAS No.	nical Substance Control
Isobutane	10 to 20	75-28-5	(2)-4
n-butane	20 to 30	106-97-8	(2)-4
Propane	20 to 30	74-98-6	(2)-3

Note: These values are not specification values.

Reference Number: 150925-BH1

Prepared: 2012年6月10日 Revised: 2018年3月30日

Product name: H1 Bell Hammer Spray 420 ml

Refer to "15. Applicable laws" for ingredients applicable to Industrial Safety and Health Law and Law concerning Pollutant Release and Transfer Register (PRTR).

4. First aid measures

If inhaled: Move to an area of fresh air and keep at rest in a position comfortable for breathing.

Call a doctor if you feel unwell.

If on skin: Immediately wipe off with a clean dry cloth.

Do not use solvent or thinner. Wash with plenty of water and soap.

If there is a change in appearance, if there is stimulation or pain or if you feel sick, consult a

physician.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to

do. Continue rinsing.

Ensure that water reaches all areas of the eyes. If eye irritation persists, get medical advice/attention.

If swallowed: Do not swallow vomit.

Do not induce vomiting unless directed by a doctor.

Rest and consult a physician immediately.

Protection of first-aiders: Anyone helping the injured person should wear protective equipment such as rubber gloves and

sealed goggles.

5. Firefighting measures

Extinguishing media Appropriate extinguishing media.

In case of fire, use foam, powder or carbon dioxide.

commendations on fire extinguish Specific fire fighting methods:

Spray water on sealed containers that have been exposed to high temperatures to cool.

Conduct fire fighting activities from a windward location. Immediately remove flammable materials from the vicinity.

In the case of aerosol products, conduct firefighting activities at a safe distance since aerosols

may explode at high temperatures.

Protection for fire fighters Wear appropriate protective equipment (such as heat-resistant clothing).

Reference Number: 150925-BH1

Prepared: 2012年6月10日 Revised: 2018年3月30日

Product name: H1 Bell Hammer Spray 420 ml

6. Accidental release measures

Personal precautions Protective equipment and emergency measures Wear suitable protective equipment (gloves, protective mask, apron, goggles, etc.) when working

Prevent secondary disasters by prohibiting entry into the surrounding area and keeping

unauthorized persons at a distance.

Environmental precautions Precautions should be taken to prevent an impact on the environment due to the release of

spilled substances into rivers etc.

Methods and materials for containment and clean up

Recover spilled substance into a sealable container and transfer to a safe location. Dispose of debris and waste etc. in accordance with relevant laws and regulations.

Measures to prevent secondary

Install appropriate fire extinguishers in preparation for fires.

Immediately remove any ignition sources, high temperature bodies or nearby

7. Precautions for handling and storage

Handling

Technical Prevention of exposure of handler

Avoid inhalation of dust, smoke, gas, mist, vapor or spray.

(Prevention of fire/explosion)

Avoid ignition sources such as heat, sparks, open flames or high temperatures. No smoking.

Do not spray on open flames or other ignition sources.

Precautions for safe handling

Use only outdoors or in well-ventilated areas.

Wear protective gloves, protective clothing, protective goggles and face shield.

Do not puncture or burn, even after use.

Incompatibilities

Appropriate storage conditions

Safe storage conditions

Store in a well-ventilated area. Keep container tightly closed. Store locked up.

Storage conditions to avoid Shield from sunlight.

Do not store at temperatures of $\geq 40^{\circ}$ C.

Reference Number: 150925-BH1

Prepared: 2012年6月10日 Revised: 2018年3月30日

Product name: H1 Bell Hammer Spray 420 ml

8. Exposure prevention and protection measures

Permissible

Name of component	Permissible Concentration		
	Japan Society for Occupational Health	ACGIH	
n-butane	500ppm (1998)	STEL: 1,000ppm (central nervous system impairment) (2012)	
Propane	Not established	Asphyxiation	
Isobutane	500ppm (1988)	STEL: 1,000ppm (central nervous system impairment) (2012)	

Exposure

Equipment measures Handle in a location with adequate ventilation.

Provide appropriate exhaust/ventilation equipment.

Protective

Respiratory Wear respiratory protection. Hand protection Wear protective gloves.

Eye protection Wear protective glasses and face protection.

Skin and body protection Wear protective clothing.

Wash contaminated areas thoroughly after handling. Hygiene measures

Do not eat, drink or smoke while using this product.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical State

Shape Liquid Color White

Odor Characteristic odor

Specific temperature/temperature range at which the physical state changes

Initial boiling

point/boiling point (Propane) -42°C

Flash point

(Propane) -104°C

Spontaneous

365°C

ignition Explosion

Ignition or explosion range

characteristics 1.8vol% Lower limit Upper limit 9.5vol%

Specific

0.64±0.02g/cm3

gravity/density

Reference Number: 150925-BH1

Prepared: 2012年6月10日 Revised: 2018年3月30日

Product name: H1 Bell Hammer Spray 420 ml

10. Stability and reactivity

Chemical stability: Aerosol can products may explode at temperatures of ≥ 40 °C.

Possibility of hazardous May react with oxidizing substances etc. if they come into contact.

Conditions to avoid: Avoid heating, sparks, open flames and other ignition sources.

Incompatible hazardous Oxidizing substances.

Hazardous decomposition Harmful gases such as carbon monoxide, nitrogen oxide and other low molecular weight

monomers are generated upon combustion.

11. Toxicological information

Information on toxicological effects

Acute toxicity Isobutane gas: mouse LC50=11000 ppm/4hr (ACGIH, 2004).

Immediate effects due to short-term exposure/delayed or chronic effects due to long-term exposure

Specific target organ toxicity

Specific target organ toxicity, single

[Category

Isobutane Heart [(Category 3 (Anesthetic action)]

(n-butane) Anesthetic

action

(Propane) Anesthetic

action

(Isobutane Anesthetic

action

12. Ecological information

Water

solubility

 $(n\text{-butane}) \hspace{1.5cm} 0.0061 \; \text{g}/100 \; \text{ml} \; (20 \; \text{C}) \; (ICSC, \, 2003).$

(Propane) 0.007 g/100 ml (20 C) (ICSC, 2003).

(Isobutane) Not soluble (ICSC, 1998).

Bioaccumulative potential

(Propane) log Pow=2.36 (ICSC, 2003).

(Isobutane) log Pow=2.8 (ICSC, 1998).

Reference Number: 150925-BH1

Prepared: 2012年6月10日 Revised: 2018年3月30日

Product name: H1 Bell Hammer Spray 420 ml

> log Pow=2.89 (ICSC, 2003). (n-butane)

Other information

May impact the environment so handle spillages and disposal with care.

In particular, do not allow the product or washing water to flow directly onto the ground or

13. Disposal considerations

Waste treatment method

Avoid release to the environment.

Dispose of contents and containers according to local and national regulations.

Do not incinerate aerosol products.

Use the entire content of aerosol products. Throw out once the gas has been completely expelled. Do this outdoors and away from fire by pushing the button until the jet sound disappears.

Never dispose of products that still contain product.

Take precautions to avoid inhaling fire or mist when expelling gas.

Contaminated containers and packaging

Do not puncture or burn, even after use.

14. Transport information

UN number, UN classification

No. 1950

Product name (UN shipping name) Aerosol, flammable

UN classification

2.1 (Hazard class in transportation)

Guideline number 126

15. Applicable laws

Safety, health and environmental regulations, laws and ordinances specific to this product.

Does not fall under the Poisonous and Deleterious Substances Control Law.

Industrial Safety and Health Law

Labeling of dangerous/harmful substances (Article 57-2, Appended table 9 of Article 18 -2 of the order). n-butane: Isobutane

Appended Table 1 Hazardous materials (Relating to Articles 1, 6 and 1: Hazardous materials/Flammable gases (Appended Table 1, Item 5 of the order).

Name notification Hazardous/harmful materials (Article 57-2, Appended table 9 of Article 18-2 of the order)

n-butane; Isobutane

Reference Number: 150925-BH1

Prepared: 2012年6月10日 Revised: 2018年3月30日

Product name: H1 Bell Hammer Spray 420 ml

Does not fall under the Law concerning Pollutant Release and Transfer Register (PRTR).

Fire Service Act

Category 4 Inflammable liquids Class 4 petroleums Danger level III.

High Pressure Gas Safety Law

Since this aerosol product has a capacity of ≤ 1 liter and a pressure of ≤ 0.8 MPa at 35°C, the

High Pressure Gas Safety Law does not apply.

Ship Safety Law

Gas Flammable gas Classification 2 Category 2.1

Civil Aeronautics Law

High pressure gas flammable gas Classification 2 Category 2.1

16. Other information

References Globally Harmonized System of Classification and Labelling of Chemicals, (5th ed., 2013),

Recommendations on the TRANSPORT OF DANGEROUS GOODS 19th edit., 2015 UN. Classification, labelling and packaging of substances and mixtures (table3-1 ECNO6182012).

2012 EMERGENCY RESPONSE GUIDEBOOK(US DOT).

2018 TLVs and BEIs. (ACGIH).

http://monographs.iarc.fr/ENG/Classification/index.php

JIS Z 7253 (2012) JIS Z 7252 (2014)

2017 Recommendations on permissible concentrations (Japan Society for Occupational

Supplier's data/information.

Limitation of liability These contents were created based on materials and information data available at the time of

preparation and may be revised by new findings. Precautions are subject to normal handling so

appropriate safety measures must be implemented in the case of special handling.